

- > Certified to the new UL 1741/IEEE 1547
- > 10 yr. standard warranty
- > Highest CEC efficiency in its class
- > Integrated load-break rated AC and DC disconnect switch
- > Integrated fused series string combiner
- > Sealed electronics enclosure & Opticool
- > Comprehensive SMA communications and data collection options
- > Ideal for residential or commercial applications
- > Sunny Tower compatible



Sunny Boy 5000 / 6000 / 7000

The best in their class

SMA is proud to introduce our new line of inverters updated with our latest technology and designed specifically to meet the new IEEE 1547 requirements. The SB6000U and SB7000U are also compatible with SMA's new Sunny Tower. Increased efficiency means better performance and shorter payback periods. All three models are field-configurable for positive ground systems making them more versatile than ever. With over 500,000 fielded units, Sunny Boy has become the benchmark for PV inverter performance and reliability throughout the world.



Technical Data

Sunny Boy 5000 / 6000 / 7000

	SB 5000US	SB 6000US	SB 7000US
Input Data (DC)			
Max. Recommended Array Input Power (DC @ STC)	6250 W	7500 W	8750 W
Max. DC Voltage	600 V	600 V	600 V
Peak Power Tracking Voltage	250 - 480 V	250 - 480 V	250 - 480 V
DC Max. Input Current	21 A	25 A	30 A
DC Voltage Ripple	< 5%	< 5%	< 5%
Number of Fused String Inputs	4	4	4
PV Start Voltage (adjustable)	300 V	300 V	300 V
Output Data (AC)			
AC Nominal Power	5000 W	6000 W	7000 W
AC Maximum Output Power	5000 W	6000 W	7000 W
AC Maximum Output Current (@ 208, 240, 277 V)	24 A, 20.8 A, 18 A	29 A, 25 A, 21.6 A	34 A, 29 A, 25.3 A
AC Nominal Voltage / Range	183 - 229 V @ 208 V 211 - 264 V @ 240 V 244 - 305 V @ 277 V	183 - 229 V @ 208 V 211 - 264 V @ 240 V 244 - 305 V @ 277 V	183 - 229 V @ 208 V 211 - 264 V @ 240 V 244 - 305 V @ 277 V
AC Frequency / Range	60 Hz / 59.3 Hz - 60.5 Hz	60 Hz / 59.3 Hz - 60.5 Hz	60 Hz / 59.3 Hz - 60.5 Hz
Power Factor	1	1	1
Efficiency			
Peak Inverter Efficiency	96.8 %	97.0 %	97.1 %
CEC weighted Efficiency	95.5 % @ 208 V 95.5 % @ 240 V 95.5 % @ 277 V	95.5 % @ 208 V 95.5 % @ 240 V 96.0 % @ 277 V	95.5 % @ 208 V 96.0 % @ 240 V 96.0 % @ 277 V
Mechanical Data			
Dimensions W x H x D in inches	18.4 x 24.1 x 9.5	18.4 x 24.1 x 9.5	18.4 x 24.1 x 9.5
Weight / Shipping Weight	143 lbs / 154 lbs	143 lbs / 154 lbs	143 lbs / 154 lbs
Ambient temperature range	-13 to +113 °F	-13 to +113 °F	-13 to +113 °F
Power Consumption: standby / nighttime	< 7 W / 0.25 W	< 7 W / 0.25 W	< 7 W / 0.25 W
Topology	PWM, true sinewave, current source	PWM, true sinewave, current source	PWM, true sinewave, current source
Cooling Concept	Convection with regulated fan cooling	Convection with regulated fan cooling	Convection with regulated fan cooling
Mounting Location Indoor / Outdoor (NEMA 3R)	● / ●	● / ●	● / ●
Features			
LCD Display	●	●	●
Lid Color: aluminum / red / blue / yellow	● / ○ / ○ / ○	● / ○ / ○ / ○	● / ○ / ○ / ○
Communication: RS485 / Wireless	○ / ○	○ / ○	○ / ○
Warranty: 10-year	●	●	●
Compliance: IEEE-929, IEEE-1547, UL 1741, UL 1998, FCC Part 15 A & B	●	●	●
Specifications for nominal conditions	● Included ○ Option – Not available		

Efficiency Curves

